



Genspec[®] GS4000

Standard Pressure Transmitter



- Suitable for the majority of industrial applications
- Pressure ranges available from 0-500 mbar to 0-700 bar
- Gauge or Absolute reference
- Reliable pressure measurement
- Long service life
- Robust yet compact designs





Genspec[®] GS4000

Standard Pressure Transmitter

Description

The Genspec GS4000 series of general-purpose pressure transducers is designed for applications where economical price and reliable pressure measurement is required. Incorporating bonded strain gauge technology and utilising unique manufacturing techniques results in a low cost, high quality transducer ideal for O.E.M applications.

Constructed from stainless steel with 17/4 PH stainless steel diaphragm for ranges above 20 bar, and a ceramic diaphragm for lower ranges, the GENSPEC series of transducers are of a robust yet compact design. Applications include the continuous monitoring of oil, gas, water and other liquids in a wide range of industries.

GENSPEC transducers are compatible with the PM8000 range of panel meters and controllers to produce a simple low cost and accurate pressure measuring and control system.


Available in pressure ranges from 0-0.5 bar to 0-700 bar, gauge or absolute and electrical outputs 0-2 mV/V, 0-5Vdc, 0-10Vdc and 4-20 mA (two wire).

Model	Dimension 'A'
GS4000/GS4100	36
GS4101,2,3	55
GS4001,2,3	64

ELECTRICAL CONNECTION (mA)	
Pin No.	2 wire
1	+supply
2	4-20mA signal
3	not fitted
⏏	to case

ELECTRICAL CONNECTION (Vdc)		
Pin No.	4 wire	3 wire
1	-supply	common
2	+supply	+supply
3	+output	+output
⏏	-output	to case

Dimensions (in mm)



Model shown GS4003



Genspec[®] GS4000

Standard Pressure Transmitter

Technical Data

Type:	GS4000/GS4100	GS4xx1	GS4xx2	GS4003/GS4103
Sensor Technology	Ceramic Thick Film or Bonded Foil Strain Gauge			
Output signal:	2 mV/V typical (4 wire)	0 - 5 V (3 or 4 wire)	0 - 10 V (3 or 4 wire)	4 - 20 mA (2 wire)
Supply Voltage:	10 VDC (5 - 15 V)	13 - 30 VDC	13 - 30 VDC	13 - 36 VDC
Pressure Reference:	Gauge (up to 700 bar) or Absolute (up to 25 bar)			
Protection of Supply Voltage:	Protected against supply voltage reversal up to 50 V (amplified versions)			
Standard Pressure Ranges (bar):	0-1 bar Vac; 0-0.5 bar; 0-1 bar; 0-10 bar; 0-25 bar; 0-100 bar; 0-250 bar; 0-700 bar (other ranges available)			
Standard Pressure Ranges (psi):	0-30 in Hg; 0-7.5 psi; 0-15 psi; 0-150 psi; 0-300 psi; 0-1,500 psi; 0-3,000 psi; 0-10,000 psi (other ranges available)			
Overpressure Safety:	1.6x from ranges -1 bar to 20 bar; 2x for ranges 25 bar to 250 bar; 1.5 for ranges 400 bar (6,000 psi) to 700 bar (10,000 psi)			
Load Driving Capability:	4-20 mA: $RL < [UB - 13 V] / 20 \text{ mA}$ (e.g. with supply voltage (UB) of 36V, max. load (RL) is 1150 Ω); 2 mV/V: n/a; 0-5 V: max. load $RL > 5 \text{ K}\Omega$; 0-10 V: max. load $RL > 10 \text{ K}\Omega$			
Accuracy NLHR:	$\leq \pm 0.4 \%$ of span BFSL			
Zero Offset and Span Tolerance:	$\pm 1.0 \%$ FS at room temperature (GS4000/GS4100: $\pm 0.2 \text{ mV}$)			
Operating Ambient Temperature:	-20 °C to +85 °C (-4 °F to +185 °F)			
Operating Media Temperature:	-20 °C to +85 °C (-4 °F to +185 °F)			
Storage Temperature:	+5 °C to +40 °C (+41 °F to +104°F) Recommended Best Practice			
Temperature Effects:	$\pm 2\%$ FS total error band for -20 °C to +70 °C. Typical thermal zero and span coefficients $\pm 0.03 \%$ FS/°C			
Electromagnetic Capability:	Emissions: EN61000-6-4; Immunity: EN61000-6-2; Certification: CE Marked			
Insulation Resistance:	$> 100 \text{ M}\Omega @ 50 \text{ VDC}$			
Response time 10-90 %:	1 ms			
Wetted Parts:	SAE 303 stainless steel, alumina and nitrile (NBR) seal for ranges up to 20 bar, and 17/4PH and SAE 303 stainless steel for ranges above 20 bar			
Pressure Media:	All fluids compatible with SAE 303 stainless steel, alumina and nitrile (NBR) seal for ranges up to 20 bar, and 17/4PH stainless steel for ranges above 20 bar			
Pressure Connection:	1/4" BSP male (G1/4) or 1/4" NPT male (others options available)			
Electrical Connection:	Mating micro DIN socket EN175301-803 Form C (ex DIN43650), a screw terminal connector rated IP65 (other options available)			



Genspec[®] GS4000

Standard Pressure Transmitter

Order Matrix

Output	Wires	Type	Electrical Connector	Pressure Range	Process Connection						
2mV/V	Model above 20 bar	4									
0-5 Vdc		4				GS4001					
		3				GS4011					
0-10 Vdc		4				GS4002					
		3				GS4012					
4-20 mA	2	GS4003									
2m V/V	Model up to 20 bar	4									
0-5 Vdc		4							GS4101		
		3							GS4111		
0-10 Vdc		4							GS4102		
		3							GS4112		
4-20 mA		2							GS4103		
Electrical Connection / Option											
DIN plug and socket									-		
Cable outlet 1m screened			A								
M12 connector			B								
Cable outlet 1m screened IP67 protection			C								
Pressure Range in bar											
0-1 bar Vac				V001							
0-0.5 bar				0.05							
0-1 bar				0001							
0-10 bar				0010							
0-25 bar				0025							
0-100 bar				0100							
0-250 bar				0250							
0-700 bar				0700							
Process Connection											
1/4" BSP male (G1/4)					AB						
1/4" NPT Male					AM						

Order Number Example

GS4003-V001AB

For options not listed please contact sales team.

DISCLAIMER : ESI Technology Ltd operates a policy of continuous product development. We reserve the right to change specification without prior notice. All products manufactured by ESI Technology Ltd are calibrated using precision calibration equipment with traceability to international standards.



t. +44(0)1978 262 255
e. sales@esi-tec.com

www.esi-tec.com