



# Protran® PR3202

Low Pressure Differential Transmitter



- Wide range of low pressure ranges from 0-5 mbar
- Available for gauge reference or bi-directional measurement
- Durable designs for industrial and commercial installations
- ATEX/IECEX option available (includes M1 for mining applications)





# Protran<sup>®</sup> PR3202

Low Pressure Differential Transmitter

## Description

Our low range air differential pressure transmitter provides an accurate solution for low pressure sensing with ranges available from 0-5 mbar to 0-1,000 mbarDP. Incorporating the latest silicon sensor and electronics technologies, these 4-20 mA transmitters are fully temperature compensated for unrivalled stability at very low pressure.


Housed in an RFI shielded wall mountable box for EMC protection, these transmitters combine precise measurement for control at very low pressures, with the robustness and flexibility for industrial and commercial installations. An optional heavy-duty aluminium die-cast housing is available for the harshest environments.

Applications include flow measurement with pitot tubes, orifice plates and mass flow meters, plus static pressure measurement and control, in combustion chambers and clean rooms, or any application on air or gas requiring reliable ultra-low differential pressure measurement. Access to screw terminal electrical connections and to zero span potentiometers is by removing the front covers, making installation and on-site adjustment. Cable entry is through a compression seal gland, or optional M20 conduit fitting. Standard pressure connections are to push-on hose fittings for 4mm ID hose. Ranges available from 0-5 mbar to 0-1,000 mbar in DP, gauge reference or bi-directional. Ultra-low pressure ranges from 0-25 Pa are also available.

An optional ATEX and IECEx approved version of this product is available for explosion protection for flammable gases (zone 0), dusts (zone 20) and mining areas (group I M1).

## Dimensions (in mm)

ELECTRICAL CONNECTION (mA)	
<b>Pin No.</b>	<b>2 wire</b>
1	+supply
2	4-20mA signal
3	not fitted
⊥	to case





# Protran® PR3202

## Low Pressure Differential Transmitter

### Technical Data

Type:	PR3202	PR3203	PR3204
<b>Sensor Technology:</b>	Piezoresistive Silicon		
<b>Output signal:</b>	4-20 mA (2 wire)	0-5 V (3 wire)	0-10 V (3 wire)
<b>Supply Voltage:</b>	10-36 VDC	13-30 VDC	13-30 VDC
<b>Pressure Reference:</b>	Differential		
<b>Protection of Supply Voltage:</b>	Protected against supply voltage reversal up to 50 V		
<b>Standard Pressure Ranges (bar):</b>	0-5 mbar; 0-10 mbar; 0-20 mbar; 0-50 mbar; 0-100 mbar; 0-250 mbar; 0-500 mbar; 0-1,000 mbar (other options available)		
<b>Standard Pressure Ranges (psi):</b>	0-2 inH <sub>2</sub> O; 0-4 inH <sub>2</sub> O; 0-8 inH <sub>2</sub> O; 0-10 inH <sub>2</sub> O; 0-12 inH <sub>2</sub> O; 0-20 inH <sub>2</sub> O; 0-1 psi; 0-1.5 psi; 0-3 psi; 0-4 psi; 0-7.5 psi; 0-15 psi (other options available)		
<b>Overpressure Safety:</b>	25 mbar max. for ranges 0-5 mbar to 0-10 mbar; 200 mbar max. for ranges 0-20 mbar to 0-100 mbar; 1,200 mbar max. for ranges 0-150 mbar to 0-1,000 mbar		
<b>Common Mode (Static line pressure):</b>	375 mbar equal to both ports for ranges 0-5 to 0-10 mbar; 2 bar max. equal to both ports for ranges 0-20 mbar to 0-1,000 mbar		
<b>Load Driving Capability:</b>	4-20 mA: $RL < [UB - 13 V] / 20 \text{ mA}$ (e.g. with supply voltage (UB) of 36 V, max. load (RL) is 1150 Ω)		
<b>Accuracy NLHR:</b>	≤ ±0.3 % of span BFSL		
<b>Zero Offset and Span Tolerance:</b>	±1.0% FS at room temperature ±5% FS (approx.) adjustment via trimming potentiometers located beneath the enclosure lid		
<b>Operating Ambient Temperature:</b>	-20 °C - +70 °C (-4 °F to +158 °F)		
<b>Operating Media Temperature:</b>	-20 °C - +70 °C (-4 °F to +158 °F)		
<b>Storage Temperature:</b>	+5 °C to +40 °C (+41 °F to +104°F) Recommended Best Practice		
<b>Temperature Effects:</b>	±2.0% FS total error band for -20 °C - +70 °C. Typical thermal zero and span coefficients ±0.04% FS/ °C		
<b>ATEX/IECEX Approval (4-20mA version only):</b>	Ex II 1 G Ex ia IIC T4 Ga (zone 0) Ex II 1 D Ex ia III C T135°C Da (zone 20) Ex I M 1 Ex ia I Ma (group 1 M1)	N/A	N/A
<b>ATEX/IECEX Safety Values:</b>	U <sub>i</sub> = 28 V, I <sub>i</sub> = 119 mA, P <sub>i</sub> = 0.65 W, L <sub>i</sub> = 0.1 μH, C <sub>i</sub> = 74 nF, Temperature Range = -20°C - +70°C, Max. cable length = 45 m	N/A	N/A
<b>Electromagnetic Capability:</b>	Emissions: EN61000-6-4, Immunity: EN61000-6-2, Certification: CE Marked		
<b>Insulation Resistance:</b>	> 100 MΩ @ 50 VDC		
<b>Response time 10-90 %:</b>	1 mS		
<b>Wetted Parts:</b>	Nickel plated brass, silicone tubing, silicon diaphragm, glass filled polyamide		
<b>Pressure Media:</b>	Non-corrosive, non-ionic fluids, such as air, dry gases		
<b>Pressure Connection:</b>	4 mm I.D. hose (other options available)		
<b>Electrical Connection:</b>	Screw terminals for conductor sizes 0.2-2 mm <sup>2</sup> are located beneath the enclosure lid. Cable entry is via IP66 cable gland with compression seal for cable sizes 7-10.5 mm		



# Protran<sup>®</sup> PR3202

Low Pressure Differential Transmitter

## Order Matrix

Output	Wires	Type	Electrical Connector	Pressure Range	Process Connection
4-20mA	2	PR3202			
0-5 V	3	PR3203			
0-10 V	3	PR3204			
<b>Electrical Connection / Option</b>					
M20 Cable Gland (PR3202 only)			-		
ATEX/ IECEx certified			EX		
<b>Pressure Range in bar</b>					
0-5 mbar				0005	
0-50 mbar				0050	
0-100 mbar				0100	
0-500 mbar				0500	
<b>Process Connection</b>					
4.8mm tube connection (push-on stem)					AW
1/4" BSP male (G1/4)					AB

### Order Number Example

PR3202EX0005AR

For options not listed please contact sales team.

**DISCLAIMER :** ESI Technology Ltd operates a policy of continuous product development. We reserve the right to change specification without prior notice. All products manufactured by ESI Technology Ltd are calibrated using precision calibration equipment with traceability to international standards.



t. +44(0)1978 262 255

e. sales@esi-tec.com

[www.esi-tec.com](http://www.esi-tec.com)